

4315 Airwest Dr. SE; Kentwood, MI 49512 Phone: 616-554-9555 Fax: 616-554-9898 www.doylevacuum.com

Free-Use Vacuum



Ideal for...

- Fleet Maintenance Facilities
- Quick-Lubes
- Car and Truck Rental Facilities
- Automotive Dealerships and Repair Facilities
- Car Washes
- Gas Stations & Convenience Stores
- Other...

Quality - Performance - Reliability

Several models to choose from, depending on your specific application needs...

Model 210000 – No Switch or Timer (For Remote Switch)

Model 210100 - ON/OFF Toggle Switch

Model 210200 - Push Button Switch with Timer

Available Motor Options:

(2) Standard Motors	120 Volts / 18 Amps
(2) High-Performance Motors	120 Volts / 24 Amps
(3) Standard Motors	120 Volts / 27 Amps
(2) High-Performance Motors	240 Volts / 13 Amps

Model 210350 – No Switch or Timer (For Remote Switch)

Model 210450 – ON/OFF Toggle Switch

Model 210550 - Push Button Switch with Timer

Available Motor Options:

(3) High-Performance Motors 240 Volts / 19 Amps





On the back of the machine - the upper door opens to allow access to the filter/intake chamber – the lower door opens to allow access to the removable five gallon dirt bucket

Standard Features:

- Stainless steel construction
- 3-Chamber vacuum tank with separate dirt intake and collection chambers
- Two pleated cartridge filters provide 16 ft² of filter surface area – with expanded-PTFE surface membrane, filters are 99.7% efficient at 0.3 microns
- 5-Gallon bucket for dirt compartment
- Low voltage (24-Volt) control circuit
- Fuse Protected

Dimensions: 20.0" Wide x 24.0" Deep x 52.0" Tall

Weight: Approximately 125 lbs.