

# PORTABLE POWER VAC

Commercial Duty – Wet/Dry Vacuums



Dual-Motor Vacuum Unit with Floor Wand / Brush and Standard Heavy-Duty Polyethylene Tank



Dual-Motor Vacuum Unit with Floor Wand / Brush and Optional 55-Gallon Drum Adapter (Drum not Included)

## Quality - Performance - Reliability

Several models to choose from, depending on your specific application and power requirements...

### Model 7100-HP-240 (Single Motor)

- 220-240 Volts / 5.4 Amps
- 109 CFM (Airflow) / 100 Inches H<sub>2</sub>O (Suction)
- 372 Maximum Air Watts

### Model 7100-HP-120 (Single Motor)

- 110-120 Volts / 11.3 Amps
- 112 CFM (Airflow) / 104 Inches H<sub>2</sub>O (Suction)
- 395 Maximum Air Watts

### Model 7200-STD-120 (Dual Motor)

- 110-120 Volts / 15.0 Amps
- 173 CFM (Airflow) / 84 Inches H<sub>2</sub>O (Suction)
- 506 Maximum Air Watts

### Model 7200-HP-240 (Dual Motor)

- 220-240 Volts / 10.8 Amps
- 196 CFM (Airflow) / 100 Inches H<sub>2</sub>O (Suction)
- 670 Maximum Air Watts

### Model 7200-HP-120 (Dual Motor)

- 110-120 Volts / 22.0 Amps
- 202 CFM (Airflow) / 104 Inches H<sub>2</sub>O (Suction)
- 711 Maximum Air Watts

### Standard Features:

- Powder Coated Powerhead Assembly
- By-Pass Cooled Motors with Epoxy Coating on Fan Case and Air-Seal on Motor Bearings
- **Pleated Cartridge Filter with Expanded-PTFE Surface Membrane is 99.7% Efficient at 0.3 microns (Drywall Dust is Approximately 0.5 microns). HEPA Grade.**
- Rugged 18 Gallon Polyethylene Tank (or Powder Coated 55-Gallon Drum Adapter)
- 25' Power Cord
- Upholstery Tool and Crevice Tool
- 1.5" x 15' Crush Proof Hose (Single Motor Models)
- 2.0" x 15' Crush Proof Hose (Dual Motor Models)

### Options:

- 25' and 50' Crush Proof Hoses (1.5" and 2.0")
- Floor Wand and Tools (i.e. Floor Brushes, Squeegees, Carpet Tools, Air Turbine Carpet Tools, etc.)

**DOYLE**

**DOYLE VACUUM SYSTEMS, LLC**

4315 Airwest Dr. SE; Kentwood, MI 49512

Phone: 616-554-9555 Fax: 616-554-9898

[www.doylevacuum.com](http://www.doylevacuum.com)